

# STRAIGHT THROUGH JOINT BOX SAKOP M-6/PT FOR VOLTAGES UP TO 3.6/6 kV

## APPLICATION AREA

- The kit for connection of three core electric power cables designed for rated voltage of 3.6/6 kV, wrapped in paper insulation soaked with non-dripping compound and protected with lead armour of the H(A)KnyFtA(y)... type
- Enables connection of cables with different cross-section of working cores ranging from 25 to 240 mm<sup>2</sup>
- Suitable for direct burying into ground



## TECHNICAL PARAMETERS

- Working cores can be connected together by means of crimped terminals or terminals with secure lock bolts (supplied upon request)
- Cable insulation is restored by means of self-bonding adhesive tape for high voltages
- Restoration of the return line by means of PLC woven copper tape
- Outer sheath is made of a stud tube or a heat shrink crust
- Each kit comprises all components and instruction manuals for making the joint
- The joint box can be connected to live voltage right after installation

## SPECIFICATION

Type	Cross-section [mm <sup>2</sup> ]	Outer sheath
SAKOP M-6/PT-1	25 – 70	heat shrink stud tube
SAKOP M-6/PT-2	95 – 120	heat shrink stud tube
SAKOP M-6/PT-3	150 – 240	heat shrink stud tube
SAKOP M-6/PT-4	25 – 70	heat shrink crust
SAKOP M-6/PT-5	95 – 120	heat shrink crust
SAKOP M-6/PT-6	150 – 240	heat shrink crust

## COMPLETED JOINT BOX



v.2