

# INTERFACING JOINT BOX SAKOP M-6/PYT FOR VOLTAGES UP TO 3.6/6 kV

## APPLICATION AREA

- The kit for connection of three core electric power cables designed for rated voltage of 3.6/6 kV protected by soft PVC insulation of the Y(A)KY(Fty)... type with three core electric power cables wrapped in paper insulation soaked with non-dripping substance and coated in lead armour H(A)KnyFtA(y)...
- Enables connection of cables with different cross-section of working cores ranging from 16 to 240 mm<sup>2</sup>
- Suitable for direct burying into ground



## TECHNICAL PARAMETERS

- Working cores can be connected together by means of crimped terminals or terminals with secure lock bolts (supplied upon request)
- Cable insulation is restored by means of self-bonding adhesive tape for high voltages
- Restoration of the return line by means of PLC woven copper tape
- Outer encapsulation is made of a heat shrink tube stud or coiled crust
- Each kit comprises all components and instruction manuals for making the joint
- The joint box can be connected to live voltage right after installation

## SPECIFICATION

Type	Cross-section [mm <sup>2</sup> ]	Outer sheath
SAKOP M-6/PYT-1	16 – 70	heat shrink stud tube
SAKOP M-6/PYT-2	95 – 120	heat shrink stud tube
SAKOP M-6/PYT-3	150 – 240	heat shrink stud tube
SAKOP M-6/PYT-4	16 – 70	heat shrink crust
SAKOP M-6/PYT-5	95 – 120	heat shrink crust
SAKOP M-6/PYT-6	150 – 240	heat shrink crust

## COMPLETED JOINT BOX



v.2