

STRAIGHT THROUGH JOINT BOX SAKOP M-6/T FOR VOLTAGES UP TO 3.6/6 kV

APPLICATION AREA

- The kit for connection of three core electric power cables designed for rated voltage of 3.6/6 kV and sheathed in Y(A)KY(Fty) ... soft PVC insulation;
- Enables connection of cables with different cross-section of working cores ranging from 16 to 240 mm²
- Suitable for direct burying into ground



TECHNICAL PARAMETERS

- Working cores can be connected together by means of crimped terminals or terminals with secure lock bolts (supplied upon request)
- Cable insulation is restored by means of self-bonding adhesive tape for high voltages
- Restoration of the return line:
 - cables with the return line made of Cu wires – by means of a crimped terminal or a terminal with secure lock bolts (supplied upon request);
 - cables with the return line made of Cu band – by means of PLC woven copper tape
- Cores in return lines of cables are connected together by means of crimped terminals or terminals with secure lock bolts (supplied upon request);
- Outer sheath is made of a stud tube or a heat shrink crust
- Each kit comprises all components and instruction manuals for making the joint
- The joint box can be connected to live voltage right after installation

SPECIFICATION

Type	Cross-section [mm ²]	Outer sheath
SAKOP M-6/T-1	16 – 70	heat shrink stud tube
SAKOP M-6/T-2	95 – 120	heat shrink stud tube
SAKOP M-6/T-3	150 – 240	heat shrink stud tube
SAKOP M-6/T-4	16 – 70	heat shrink crust
SAKOP M-6/T-5	95 – 120	heat shrink crust
SAKOP M-6/T-6	150 – 240	heat shrink crust

For larger cross-sections of repair kits please consult the manufacturer

COMPLETED JOINT BOX



v.2